

Crew Camp Little Lodge Series

Standard Specifications

- 8" I-Beam Main Frame with 8" Detachable Hitch (LiL' Lodge 1)
- 10" I-Beam Main Frame with 10" Detachable Hitch (LiL' Lodge 2 or Above)
- Triple Axles (LiL' Lodge 1) or Quad Axles (LiL' Lodge 2 or Above) On All Full Size Models
- Featuring 2 Brake and 1 Idle
- 2 X 6 Floor Joists 16" O.C.
- 3/4" Tongue & Groove Sub- Floor
- 2 X 4 Exterior Walls 16" O.C.
- 84" Sidewall Height (Model with NO LOFT)
- 96" Sidewall Height (Model WITH LOFT)
- Truss Rafters 16" O.C.
- 2 X 4 Bottom Plate & Double 2 X 4 Top Plate
- Front & Rear Overhangs W/ Vented Soffit
- 1/2" OSB Roof Decking
- 15# Felt Roof Underlayment
- 29 Gauge Colored Metal Roof (Choice of Green, Red or Brown Only)
- Deluxe Insulation Package: R-19 Floors, R-11 In Walls, R-19 In Roof
- Cathedral Ceiling Throughout (Except on Loft Models)
- Exterior Wrapped In 7/16" OSB Prior To Final Exterior Placement
- Real Wood Log Exterior Stained, Sealed And Caulked
- 6 / 12 Roof Pitch
- Real Wood Cedar Paneling Throughout
- Thermal Windows With Tilt Sash And Mullions
- 3/4" Pre-Finished Hardwood Flooring Throughout
- 52" Rustic Style Ceiling Fan W/ Light Kit In Living Room
- Under Counter Refrigerator (LiL' Lodge 1)
- 18 Cu. Ft. Refrigerator (LiL' Lodge 2 or Above)
- 30" Electric Or Gas Range With Full Size Oven
- Range Hood W/ Power Exhaust Fan Vented To Outside
- Custom Hand Crafted Cedar Cabinets
- Mica Counter Tops
- Stainless Steel Sink
- 20 Gallon Electric Water Heater
- 32" Fiberglass Shower (Based On Floor Plan) OR
- 54" Tub & Shower Combo (Based On Floor Plan)
- Built-In Medicine Cabinet
- Elongated Toilet
- Towel Bar And Toilet Paper Holder
- Bathroom Light & Exhaust Fan
- Smoke Alarms (2)
- Deluxe Valance Package
- Mini-Blinds Installed Throughout
- Exterior 110v Electrical Outlet (1)
- Exterior Water Spigot (1)
- Cottage Door (Per Floor Plan)
- Exterior Coach Light